10300 liter tank i Syrafast 316



139 000 SEK /st exkl moms

Article type: second-hand storage tank
Additional information: Year of manufacture 2025; Tank in very good condition; Drawing on request
Volumetric volume (L): 10.300 L
Max. density P (kg/m³): 1.000
Pressure in tank: ATM - atmosferic

Max. temperature (°C): 100 °C
Material wet parts: SS AISI 316L (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Insulation: yes
Mobile tank: no
Top type: conical
Shape of tank: cylindrical
Bottom type: flat

Total discharge: no
Fixation points: 4 attachment points
Insulation material: PIR
Outer jacket (ornamental wall): RVS 304L
Manway(s): RVS 316

Gasket manway(s): EPDM
Fixation point(s): RVS 304L
Suitable for food industry: yes
Documents included: no
Technical drawing included: yes

Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1
Position of manway: cylinder
Height manhole 1 (mm): 432 mm x H 532 mm

Hinged lid: yes
Tank outlet: inside Ø 60 mm
Agitator: no, optional
Top: 3 mm
Cylinder: 3 mm

Bottom: 5 mm
Top: 3
Insulation top: yes
Cylinder: 3
Insulation body: yes

finish of the outer jacket: welded
Insulation thickness: 80
Internal diameter tank: 2.100 mm
Distance from outlet to ground: 145 mm

Outer diameter tank: 2.280 mm

Cylinder height: 3.000 mm
Total height of tank: 3.300 mm
Empty weight tank: 1.850

SKU: 580472

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: insulated
Max. arbetstemperatur: 100 °C
Maximal densitet för produkten: 1000
Mobil tank: Nej
Övrig information: Year of manufacture 2025; Tank in very good condition; Drawing on request
Omrörare: Nej
Tankens form: cylindrical
Total urtappning: Nej
Typ av botten: flat
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316L (V4A)
Volym i liter: 10300

Utrustning
Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 60 mm
Teknisk ritning finns: Ja

Översikt material
Material: Syrafast 316
Fixeringspunkt(er): RVS 304L
Isoleringsmaterial: PIR
Ytterbeklädnad: RVS 304L

Dimensioner av tank
Cylinderhöjd: 3.000 mm
Invändig diameter: 2.100 mm
Mått utlopp till marken: 145 mm
Total höjd: 3.300 mm
Ytterdiameter: 2.280 mm

Tjocklek på tank
Botten: 5 mm
Cylinder: 3 mm
Topp: 3 mm

Tjocklek på ytterbeklädnad och isolering
Finish utvändig mantel: welded
Isolering mantel: Ja
Isoleringsmaterial: PIR

Mer

Cylinder OW: 3
Isoleringsmaterial: Ja
Isoleringstjocklek OW: 80
Isolerad: Ja
Vikt: 1.850

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se