10450 liter tank i Syrafast 316



217 000 SEK /st exkl moms

Volumetric volume (L): 10.450 L
Pressure in tank: pressure
Max. temperature (°C): 120 °C
Material wet parts: SS AISI 304 (V2A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Volume: 34 L
Max Overpressure: 3 Bar
Max. working temperature: 120 °C
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: yes
Position of manway: headside
Outlet of tank: DN80 DIN 11851
Cylinder: 3 mm

Bottom: 3 mm
Internal diameter tank: 2.450 mm
Cylinder height: 2.000 mm
Total height of tank: 3.150 mm
Empty weight tank: 1.200

SKU: 422855

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 120 °C
Mobil tank: Nej
Omrörare: Nej
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 10450

Utrustning

Dokument finns: Nej
Fläns för omrörare: Ja
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 2.000 mm
Invändig diameter: 2.450 mm
Total höjd: 3.150 mm

Tjocklek på tank

Botten: 3 mm
Cylinder: 3 mm

Mer
Isolerad: Nej
Vikt: 1.200