

1050 liter tank i Syrafast 316



189,000,00 kr /st exkl moms

Additional information: Outlet DN 60 DIN 11851; reinforcement ribs inside under the upper bottom (removable); 2 fork pockets on the outside of the lower bottom

Volumetric volume (L): 1.050 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 180 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: no

Max Overpressure: 2 Bar

Max. working temperature: 180 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: yes

Internal diameter tank: 1.350 mm

Outer diameter tank: 1.550 mm

Total height of tank: 1.530 mm

SKU: 282934

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosfäric

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 180 °C

Mobil tank: Nej

Övrig information: Outlet DN 60 DIN 11851; reinforcement ribs inside under the upper bottom (removable); 2 fork pockets on the outside of the lower bottom; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Total urtappning: Nej

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1050

Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 1.350 mm

Total höjd: 1.530 mm

Ytterdiameter: 1.550 mm

Mer

Isolerad: Ja

