105000 liter tank i Syrafast 316



485 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type TZN-SE
Additional information: Pictures of an identical tank with a smaller capacity, pls look at the technical drawing
Volumetric volume (L): 105.000 L
Max. density P (kg/m³): 1.250
Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Insulation: no

Mobile tank: no
Top type: conical 14 °
Shape of tank: cylindrical
Bottom type: flat °
Total discharge: yes

Outer jacket (ornamental wall): RVS 316
Gasket manway(s): EPDM
Valve: RVS 316L
Fixation point(s): RVS 304
Suitable for food industry: yes

Documents included: no
Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1

Position of manway: cylinder
CIP spray ball: no
Tank outlet: inside Ø 80 mm
Outlet type: DIN11851
Total outlet valve: no, optional

Agitator: no
Top: 2 mm
Cylinder: 3 mm
Bottom: 3 mm
Distance from outlet to ground: 150 mm

Outer diameter tank: 3.342 mm
Cylinder height: 12.000 mm
Total height of tank: 12.500 mm
Empty weight tank: 3.000

SKU: 376073

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Nytillverkad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: single-skin
Maximal densitet för produkten: 1250
Mobil tank: Nej
Övrig information: Pictures of an identical tank with a smaller capacity, pls look at the technical drawing
Omrörare: Nej
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: flat °
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 105000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
med besiktning av: No Documentation
Tankutlopp: inside Ø 80 mm
Teknisk ritning finns: Ja
Utloppstyp: DIN11851

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304
Ytterbeklädnad: RVS 316

Dimensioner av tank

Cylinderhöjd: 12.000 mm
Mått utlopp till marken: 150 mm
Total höjd: 12.500 mm
Ytterdiameter: 3.342 mm

Tjocklek på tank

Botten: 3 mm
Cylinder: 3 mm
Topp: 2 mm

Mer

Isolerad: Nej
Vikt: 3.000