

105000 liter tank i Syrafast 316



495,000,00 kr /st exkl moms

item available on order

Article type: brand new storage tank - type TZN-SE

Additional information: Pictures of an identical tank with a smaller capacity, pls look at the technical drawing

Volumetric volume (L): 105.000 L

Max. density P (kg/m³): 1.250

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin



Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical 14 °

Shape of tank: cylindrical

Bottom type: flat °

Total discharge: yes

Outer jacket (ornamental wall): RVS 316

Gasket manway(s): EPDM

Valve: RVS 316L

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: yes

Registration plate on the tank: yes

Inspection of: No Documentation

Flange for agitator: no

Number of manways: 1

Position of manway: cylinder

CIP spray ball: no

Tank outlet: inside Ø 80 mm

Outlet type: DIN11851

Total outlet valve: no, optional

Agitator: no

Top: 2 mm

Cylinder: 3 mm

Bottom: 3 mm

Distance from outlet to ground: 150 mm

Outer diameter tank: 3.342 mm

Cylinder height: 12.000 mm

Total height of tank: 12.500 mm

Empty weight tank: 3.000

SKU: 376073

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Maximal densitet för produkten: 1250

Mobil tank: Nej

Övrig information: Pictures of an identical tank with a smaller capacity, pls look at the technical drawing

Omrörare: Nej

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: flat °

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 105000



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
med besiktning av: No Documentation
Tankutlopp: inside Ø 80 mm
Teknisk ritning finns: Ja
Utloppstyp: DIN11851

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304
Ytterbeklädnad: RVS 316

Dimensioner av tank

Cylinderhöjd: 12.000 mm
Mått utlopp till marken: 150 mm
Total höjd: 12.500 mm
Ytterdiameter: 3.342 mm

Tjocklek på tank

Botten: 3 mm
Cylinder: 3 mm
Topp: 2 mm

Mer

Isolerad: Nej
Vikt: 3.000