10589 liter tank i Rostfritt 304



202 000 SEK /st exkl moms

Additional information: Fastening of the manhole cover incomplete; small dents in the insulating jacket
Volumetric volume (L): 10.589 L
Pressure in tank: pressure
Material wet parts: SS AISI 304 (V2A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Volume: 160 L
Max Overpressure: 3 Bar
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: 65

Agitator: yes
Number of revolutions: 7.7 / 16
Power: 1.6 / 3.3
Internal diameter tank: 2.020 mm
Outer diameter tank: 2.170 mm

Cylinder height: 2.950 mm
Total height of tank: 4.850 mm

SKU: 487052

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Mobil tank: Nej
Övrig information: Dairy; Incomplete fastening of the manhole cover; small dents in the insulation jacket; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 10589

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 2.950 mm
Invändig diameter: 2.020 mm
Total höjd: 4.850 mm
Ytterdiameter: 2.170 mm

Omrörare
Kraft (kW): 1.6 / 3.3
Varvtal: 7.7 / 16

Mer
Isolerad: Ja