

1085 liter tank i Syrafast 316



99,000 SEK /st exkl moms

Additional information: Biochemistry; Welded stainless steel ring around the outside of the vessel (protrudes approx. 100 mm from the outer diameter (insulation)); some residues of previous content

Volumetric volume (L): 1.085 L

Pressure in tank: ATM - atmospheric

Max. temperature (°C): 95 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 17 L

Max Overpressure: 3,50 Bar

Max. working temperature: 143 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 48

Agitator: yes

Power: 1,10

Internal diameter tank: 990 mm

Outer diameter tank: 1.130 mm

Cylinder height: 1.240 mm

Total height of tank: 2.150 mm

SKU: 564685

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosfäric

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 95 °C

Mobil tank: Nej

Övrig information: Biochemistry; Welded stainless steel ring around the outside of the vessel (protrudes approx. 100 mm from the outer diameter (insulation)); some residues of previous content; we can't give any

Övrig information2: guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1085

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.240 mm

Invändig diameter: 990 mm

Total höjd: 2.150 mm

Ytterdiameter: 1.130 mm

Omrörare

Kraft (kW): 1,10

Mer

Isolerad: Ja
