

## 10875 liter tank i Rostfritt 304



**217 000 SEK /st exkl moms**

**Additional information:** Adhesive industry; Support ring made of Fe; some of the flanges of the upper bottom were welded to the inside with a stainless steel sheet by the previous operator (and an opening was cut in some of these sheets; see photos); manhole diameter 480 mm; some residues of previous content; manhole cover is missing

**Volumetric volume (L):** 10.875 L

**Pressure in tank:** vacuum

**Max. pressure (Bar):** 6 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 330 L

**Max Overpressure:** 20 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 220 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Heat exchanger:** RVS 304

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** available

**Agitator:** yes

**Number of revolutions:** 78

**Power:** 22

**Top:** 14 mm

**Cylinder:** 8,70 mm

**Bottom:** 11,40 mm

**Internal diameter tank:** 2.170 mm

**Cylinder height:** 2.200 mm

**Total height of tank:** 5.050 mm

**SKU:** 274105

## Mer information

### Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Adhesive industry; Support ring made of Fe; some of the flanges of the upper bottom were welded to the inside by the previous operator with a stainless steel sheet (and an opening was sometimes cut

Övrig information2: into these sheets; see photos); diameter manhole 480 mm; some residues of previous content; manhole cover is missing; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 10875



## Utrustning

Dokument finns: Nej  
Fläns för omrörare: Nej  
Märkskylt: Ja  
Teknisk ritning finns: Nej

## Översikt material

Material: Rostfritt 304

## Dimensioner av tank

Cylinderhöjd: 2.200 mm  
Invändig diameter: 2.170 mm  
Total höjd: 5.050 mm

## Omrörare

Kraft (kW): 22  
Varvtal: 78

## Tjocklek på tank

Botten: 11,40 mm  
Cylinder: 8,70 mm  
Topp: 14 mm

## Mer

Värmeväxlare: RVS 304  
Isolerad: Nej