10875 liter tank i Rostfritt 304



218 000 SEK /st exkl moms

Additional information: Adhesive industry; Support ring made of Fe; some of the flanges of the upper bottom were welded to the inside with a stainless steel sheet by the previous operator (and an opening was cut in some of these sheets; see photos); manhole diameter 480 mm; some residues of previous content; manhole cover is missing
Volumetric volume (L): 10.875 L

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Pressure in tank: pressure and vacuum
Max. pressure (Bar): 6 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 330 L
Max Overpressure: 20 Bar

Max onderdruk: 1 Bar
Max. working temperature: 220 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Heat exchanger: RVS 304

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside

Outlet of tank: available
Agitator: yes
Number of revolutions: 78
Power: 22
Top: 14 mm

Cylinder: 8,70 mm
Bottom: 11,40 mm
Internal diameter tank: 2.170 mm
Cylinder height: 2.200 mm
Total height of tank: 5.050 mm

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

SKU: 398219

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Adhesive industry; Support ring made of Fe; some of the flanges of the upper bottom were welded to the inside by the previous operator with a stainless steel sheet (and an opening was sometimes cut
Övrig information2: into these sheets; see photos); diameter manhole 480 mm; some residues of previous content;manhole cover is missing; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 6 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 10875

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Utrustning
Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material
Material: Rostfritt 304

Dimensioner av tank
Cylinderhöjd: 2.200 mm
Invändig diameter: 2.170 mm
Total höjd: 5.050 mm

Omrörare
Kraft (kW): 22
Varvtal: 78

Tjocklek på tank
Botten: 11,40 mm
Cylinder: 8,70 mm
Topp: 14 mm

Mer
Värmeväxlare: RVS 304
Isolerad: Nej