

10875 liter tank i Rostfritt 304



219,000,00 kr /st exkl moms

Additional information: Adhesive industry; Support ring made of Fe; some of the flanges of the upper bottom were welded to the inside by the previous operator with a stainless steel sheet (and an opening was sometimes cut into these sheets; see photos); diameter manhole 480 mm; some residues of previous content; manhole cover is missing

Volumetric volume (L): 10.875 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 330 L

Max Overpressure: 20 Bar

Max onderdruk: 1 Bar

Max. working temperature: 220 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: available

Agitator: yes

Number of revolutions: 78

Power: 22

Top: 14 mm

Cylinder: 8,70 mm

Bottom: 11,40 mm

Internal diameter tank: 2.170 mm

Cylinder height: 2.200 mm

Total height of tank: 5.050 mm

SKU: 274105

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Adhesive industry; Support ring made of Fe; some of the flanges of the upper bottom were welded to the inside by the previous operator with a stainless steel sheet (and an opening was sometimes cut

Övrig information2: into these sheets; see photos); diameter manhole 480 mm; some residues of previous content; manhole cover is missing; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 10875



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 2.200 mm
Invändig diameter: 2.170 mm
Total höjd: 5.050 mm

Omrörare

Kraft (kW): 22
Varvtal: 78

Tjocklek på tank

Botten: 11,40 mm
Cylinder: 8,70 mm
Topp: 14 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Nej