

## 1100 liter tank i Syrafast 316



**43 000 SEK /st exkl moms**

**Additional information:** food industry; Build-up and metallic discoloration inside the vessel; lid made of 1.4301 (stainless steel 304); motor-/gear is missing

**Volumetric volume (L):** 1.100 L

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 134 °C  
**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical  
**Configuration:** insulated  
**Heat exchanger:** no  
**Insulation:** yes  
**Mobile tank:** no

**Total discharge:** yes  
**Volume:** 125 L  
**Max Overpressure:** 3 Bar  
**Max. working temperature:** 134 °C  
**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket  
**Heat exchanger:** RVS 304  
**Documents included:** no  
**Technical drawing included:** no  
**Registration plate on the tank:** yes

**Flange for agitator:** no  
**Outlet of tank:** 100  
**Agitator:** yes  
**Internal diameter tank:** 990 mm  
**Outer diameter tank:** 1.150 mm

**Cylinder height:** 1.500 mm  
**Total height of tank:** 2.450 mm

**SKU:** 272302

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosfERIC

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 134 °C

Mobil tank: Nej

Övrig information: food industry; adhesions and metallic discolourations inside the tank; tank cover made of 1.4301 (aisi 304); motor-/gear is missing; we can't give any guarantees about the heating/cooling jacket; we

Övrig information2: can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1100

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

### Dimensioner av tank

Cylinderhöjd: 1.500 mm

Invändig diameter: 990 mm

Total höjd: 2.450 mm

Ytterdiameter: 1.150 mm

**Mer**

Värmeväxlare: RVS 304

Isolerad: Ja