

1100 liter tank i Syrafast 316



243 000 SEK /st exkl moms

Additional information: Pharmacy; 3 loose load cells (no guarantee of functionality) are included in the scope of delivery; Metallic discolouration inside

Volumetric volume (L): 1.100 L

Pressure in tank: vacuum

Max. pressure (Bar): 1,99 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 122 L

Max Overpressure: 3 Bar

Max. working temperature: 130 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 38

Agitator: yes

Number of revolutions: 394

Power: 0,75

Top: 4,50 mm

Cylinder: 8 mm

Bottom: 5,40 mm

Internal diameter tank: 988 mm

Outer diameter tank: 1.154 mm

Cylinder height: 875 mm

Total height of tank: 2.600 mm

SKU: 300086

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 130 °C

Mobil tank: Nej

Övrig information: Pharmacy; 3 loose load cells (no guarantee of functionality) are included in the scope of delivery; Metallic discolouration inside; we can't give any guarantees about the heating/cooling jacket; we

Övrig information2: can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 1,99 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1100

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 875 mm

Invändig diameter: 988 mm

Total höjd: 2.600 mm

Ytterdiameter: 1.154 mm

Omrörare

Kraft (kW): 0,75

Varvtal: 394

Tjocklek på tank

Botten: 5,40 mm

Cylinder: 8 mm

Topp: 4,50 mm

Mer

Isolerad: Ja