11000 liter tank i Syrafast 316



100 000 SEK /st exkl moms

Additional information: Solvents; Manufactured in accordance with DIN6618; test report for decommissioning in accordance with VAwS available; piping inside the vessels; stand frame made of 1.4301 (stainless steel 304); manhole cover made of 1.4541 (stainless steel 304); outlet with screwed-on reducer
Volumetric volume (L): 11.100 L
Pressure in tank: pressure and vacuum

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. pressure (Bar): 0,30 Bar
Min. pressure (Bar): 0,10 Bar

Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no

Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Position of manway: headside
Outlet of tank: flange DN50
Top: 2,50 mm
Cylinder: 3 mm

Bottom: 2,80 mm
Internal diameter tank: 2.000 mm
Cylinder height: 3.000 mm
Total height of tank: 4.750 mm

SKU: 413438

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: Solvents; Built according to DIN6618; pipelines inside the tanks; stand frame, 1.4301 (Aisi 304); manhole cover, 1.4541 (Aisi 304); Outlet with screwed reduction
Övrig information2: reducer
Omrörare: Nej
Övertryck: 0,30 Bar
Total urtappning: Ja
Undertryck (vakuum): 0,10 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 11100

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 3.000 mm
Invändig diameter: 1.980 mm
Total höjd: 4.750 mm

Tjocklek på tank
Botten: 3,90 mm
Cylinder: 3 mm
Topp: 2,50 mm

Mer
Isolerad: Nej