


11000 liter tank i Syrafast 316



99,000,00 kr /st exkl moms

Additional information: Solvents; Built according to DIN6618; pipelines inside the tanks; stand frame, 1.4301 (Aisi 304); manhole cover, 1.4541 (Aisi 304); Outlet with screwed reduction

Volumetric volume (L): 11.100 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 0,30 Bar

Min. pressure (Bar): 0,10 Bar

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN50

Cylinder: 3 mm

Bottom: 3,90 mm

Internal diameter tank: 1.980 mm

Cylinder height: 3.000 mm

Total height of tank: 4.750 mm

SKU: 289916

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: Solvents; Built according to DIN6618; pipelines inside the tanks; stand frame, 1.4301 (Aisi 304); manhole cover, 1.4541 (Aisi 304); Outlet with screwed reduction

Omrörare: Nej

Övertryck: 0,30 Bar

Total urtappning: Ja

Undertryck (vakuum): 0,10 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 11100

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 3.000 mm

Invändig diameter: 1.980 mm

Total höjd: 4.750 mm

Tjocklek på tank

Botten: 3,90 mm

Cylinder: 3 mm

Mer

Isolerad: Nej