

11424 liter tank i Rostfritt 304



177 000 SEK /st exkl moms

Additional information: Dairy; Double jacket with trickle ring - only suitable for unpressurized temperature control; dents in the double jacket; double jacket cladding partially detached in the area of the upper bottom (see photos); some residues of previous content; pipe end cut flush

Volumetric volume (L): 11.424 L



Pressure in tank: vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 145 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 48

Agitator: yes

Number of revolutions: 55 / 112

Power: 1.5 / 2.2

Cylinder: 6 mm

Bottom: 6 mm

Internal diameter tank: 2.000 mm

Outer diameter tank: 2.140 mm

Cylinder height: 3.000 mm

Total height of tank: 4.500 mm

SKU: 299728

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 145 °C

Mobil tank: Nej

Övrig information: Dairy; Double jacket with trickle ring – only suitable for pressureless cooling; bumps in the double jacket; Double jacket cladding in the area of the upper bottom partially detached (see photos);

Övrig information2: some residues of previous content; pipe end cut flush; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 11424

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304



Dimensioner av tank

Cylinderhöjd: 3.000 mm
Invändig diameter: 2.000 mm
Total höjd: 4.500 mm
Ytterdiameter: 2.140 mm

Omrörare

Kraft (kW): 1.5 / 2.2
Varvtal: 55 / 112

Tjocklek på tank

Botten: 6 mm
Cylinder: 6 mm

Mer

Isolerad: Nej