

## 11424 liter tank i Rostfritt 304



**179,000,00 kr /st exkl moms**

**Additional information:** Dairy; Double jacket with trickle ring - only suitable for pressureless cooling; bumps in the double jacket; Double jacket cladding in the area of the upper bottom partially detached (see photos); some residues of previous content; pipe end cut flush

**Volumetric volume (L):** 11.424 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3,20 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 145 °C

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** 48

**Agitator:** yes

**Number of revolutions:** 55 / 112

**Power:** 1.5 / 2.2

**Cylinder:** 6 mm

**Bottom:** 6 mm

**Internal diameter tank:** 2.000 mm

**Outer diameter tank:** 2.140 mm

**Cylinder height:** 3.000 mm

**Total height of tank:** 4.500 mm

**SKU:** 299728

## Mer information

### Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 145 °C

Mobil tank: Nej

Övrig information: Dairy; Double jacket with trickle ring – only suitable for pressureless cooling; bumps in the double jacket; Double jacket cladding in the area of the upper bottom partially detached (see photos);

Övrig information2: some residues of previous content; pipe end cut flush; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 11424

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Rostfritt 304



## Dimensioner av tank

Cylinderhöjd: 3.000 mm  
Invändig diameter: 2.000 mm  
Total höjd: 4.500 mm  
Ytterdiameter: 2.140 mm

## Omrörare

Kraft (kW): 1.5 / 2.2  
Varvtal: 55 / 112

## Tjocklek på tank

Botten: 6 mm  
Cylinder: 6 mm

## Mer

Isolerad: Nej