

1150 liter tank i Syrafast 316



50,000 SEK /st exkl moms

Additional information: petrol; Halar-coating inside (very good resistance against acids, lyes and solvents); type plate non-existent; a number of connections were changed by the former operator, among other things 1 new outlet was welded in (no coating in the weld-in area of the lower floor and in the new outlet itself; no coating in the manhole cover as well); 5-foot frame Fe (galvanized; 1 foot slightly bent); some residues of

previous content; bump at the insulation jacket

Volumetric volume (L): 1.150 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 0,60 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 120 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Max Overpressure: 0,60 Bar

Max onderdruk: 1 Bar

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 316

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: yes

Position of manway: headside

Outlet of tank: flange DN100

Cylinder: 4 mm

Bottom: 4 mm

Internal diameter tank: 1.100 mm

Outer diameter tank: 1.250 mm

Cylinder height: 870 mm

Total height of tank: 2.600 mm

Total outer width: 1.660 mm

Total outer length: 1.850 mm

SKU: 266686

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 120 °C

Mobil tank: Nej

Övrig information: petrol; Halar-coating inside (very good resistance against acids, lyes and solvents); type plate non-existent; a number of connections were changed by the former operator, among other things 1 new

Övrig information2:

Omrörare: Nej

Övertryck: 0,60 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1150

Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Nej

Teknisk ritning finns: Nej



Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 870 mm

Invändig diameter: 1.100 mm

Total höjd: 2.600 mm

Ytterdiameter: 1.250 mm

Tjocklek på tank

Botten: 4 mm

Cylinder: 4 mm

Mer

Värmeväxlare: RVS 316

Isolerad: Ja