

11650 liter tank i Syrafast 316



151 000 SEK /st exkl moms

Additional information: Pharmacy; Manhole diameter approx. 600 mm (1 opening diameter 165 mm in manhole cover); 2 bearing saddles made of Fe (painted); outlet with flanged fitting; some residues of previous content; manhole cover plated

Volumetric volume (L): 11.650 L

Pressure in tank: vacuum

Max. pressure (Bar): 2 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: horizontal

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN80

Cylinder: 8,70 mm

Bottom: 6,40 mm

Internal diameter tank: 1.980 mm

Total height of tank: 2.900 mm

Total outer length: 4.000 mm

SKU: 564304

Mer information



Beskrivning av produkt

Material: Syrafast 316

Modell: Horisontell

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmacy; Manhole diameter approx. 600 mm (1 opening diameter 165 mm in manhole cover); 2 bearing saddles made of Fe (painted); outlet with flanged fitting; some residues of previous content;manhole

Övrig information2: cover plated

Omrörare: Nej

Övertryck: 2 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 11650

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 1.980 mm

Total höjd: 2.900 mm

Tjocklek på tank

Botten: 6,40 mm

Cylinder: 8,70 mm

Mer

Isolerad: Nej