

1169 liter tank i Syrafast 316



250,000,00 kr /st exkl moms

Volumetric volume (L): 1.169 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)



Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Max Overpressure: 2,50 Bar

Max. working temperature: 140 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 0 - 12

Power: 0,75

Cylinder: 4 mm

Bottom: 4 mm

Internal diameter tank: 1.192 mm

Outer diameter tank: 1.360 mm

Cylinder height: 1.000 mm

Total height of tank: 2.250 mm

SKU: 441059

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosfERIC

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1169

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.000 mm

Invändig diameter: 1.192 mm

Total höjd: 2.250 mm

Ytterdiameter: 1.360 mm

Omrörare

Kraft (kW): 0,75

Varvtal: 0 - 12

Tjocklek på tank

Botten: 4 mm

Cylinder: 4 mm

Mer

Isolerad: Ja