

## 1169 liter tank i Syrafast 316



**197 000 SEK /st exkl moms**

**Volumetric volume (L):** 1.169 L

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 100 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Max Overpressure:** 2,50 Bar

**Max. working temperature:** 140 °C

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** yes

**Outlet of tank:** DN50 DIN 11851

**Cylinder:** 4 mm

**Bottom:** 4 mm

**Internal diameter tank:** 1.200 mm

**Outer diameter tank:** 1.360 mm

**Cylinder height:** 1.000 mm

**Total height of tank:** 1.900 mm

**Empty weight tank:** 400

**SKU:** 440858

Mer information

## Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1169

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Nej

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.000 mm

Invändig diameter: 1.200 mm

Total höjd: 1.900 mm

Ytterdiameter: 1.360 mm

## Tjocklek på tank

Botten: 4 mm

Cylinder: 4 mm

**Mer**

Isolerad: Ja

Vikt: 400

---