

## 118 liter tank i Syrafast 316



**461 000 SEK /st exkl moms**

**Additional information:** Outlet: Gemü Bottom-Seat Valve with Sampling Port

**Volumetric volume (L):** 118 L

**Pressure in tank:** vacuum

**Min. pressure (Bar):** 1 Bar



**Max. temperature (°C):** 140 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 7 L

**Max Overpressure:** 5 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 140 °C

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** available

**Agitator:** yes

**Number of revolutions:** 112 - 575

**Power:** 0,18

**Cylinder:** 5 mm

**Internal diameter tank:** 500 mm

**Cylinder height:** 450 mm

**Total height of tank:** 1.635 mm

**Total outer width:** 750 mm

**Total outer length:** 1.130 mm

**Empty weight tank:** 200

**SKU:** 705490



## Mer information

### Beskrivning av produkt

Material: Syrefast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Brukt

Arbetsstryck i tank: vakuum

Konfiguration: isolert

Max. arbetstemperatur: 140 °C

Mobil tank: Nei, det er det ikke.

Övrig information: Outlet: Gemü Bottom-Seat Valve with Sampling Port; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Undertryck (vakuum): 1 bar

Uppvärmning/kylning: Nei, det er det ikke.

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 118

### Utrustning

Dokument finns: Nei, det er det ikke.

Fläns för omrörare: Nei

Märkskylt: Ja

Teknisk ritning finns: Nei, det er det ikke.

### Översikt material

Material: Syrefast 316

### Dimensioner av tank

Cylinderhöjd: 450 mm

Invändig diameter: 500 mm

Total höjd: 1 635 mm



## Omrörare

Kraft (kW): 0,18

Varvtal: 112 – 575

## Tjocklek på tank

Cylinder: 5 mm

## Mer

Isolerad: Ja

Vikt: 200