

120 liter tank i Syrafast 316



50 000 SEK /st exkl moms

Additional information: DN 250 access port; includes complete documentation from a GMP-certified pharmaceutical manufacturing facility

Volumetric volume (L): 120 L

Pressure in tank: vacuum



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 140 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: available

Cylinder: 4 mm

Internal diameter tank: 550 mm

Cylinder height: 386 mm

Total height of tank: 1.250 mm

SKU: 706873

Mer information



Beskrivning av produkt

Material: Syrefast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Brukt

Arbetsstryck i tank: vakuum

Konfiguration: enkelthudet

Max. arbetstemperatur: 140 °C

Mobil tank: Nei, det er det ikke.

Övrig information: DN 250 access port; includes complete documentation from a GMP-certified pharmaceutical manufacturing facility

Omrörare: Nei

Total urtappning: Ja

Undertryck (vakuum): 1 bar

Uppvärmning/kylning: Nei, det er det ikke.

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 120

Utrustning

Dokument finns: Nei, det er det ikke.

Fläns för omrörare: Nei

Märkskylt: Ja

Teknisk ritning finns: Nei, det er det ikke.

Översikt material

Material: Syrefast 316

Dimensioner av tank

Cylinderhöjd: 386 mm

Invändig diameter: 550 mm

Total höjd: 1250 mm

Tjocklek på tank

Cylinder: 4 mm



Mer

Isolerad: Nei