1200 liter tank i Syrafast 316



29 000 SEK /st exkl moms

Additional information: 3-legged frame made of Fe (lacquered); support ring of the lid made of Fe; 1 circular opening in the lid (see photos); some residues of previous content
Volumetric volume (L): 1.200 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Outlet of tank: 75

Agitator: yes
Number of revolutions: 1.410
Power: 0,74
Top: 2 mm
Cylinder: 1,80 mm

Bottom: 2 mm
Internal diameter tank: 1.250 mm
Cylinder height: 1.000 mm
Total height of tank: 3.000 mm

SKU: 402308

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: 3-legged frame made of Fe (lacquered); support ring of the cover made of Fe; 1 circular opening in the lid (see photos) ; some residues of previous content; we can't give any guarantees about the
Övrig information2: agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1200

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.000 mm
Invändig diameter: 1.250 mm
Total höjd: 3.000 mm

Omrörare

Kraft (kW): 0,74
Varvtal: 1.410

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tjocklek på tank
Botten: 2 mm
Cylinder: 1,80 mm
Topp: 2 mm

Mer
Isolerad: Nej