

1200 liter tank i Syrafast 316



149 000 SEK /st exkl moms

Additional information: Pharmacy; Tank was converted in 1987; manhole diameter 390 mm; further technical documents available

Volumetric volume (L): 1.200 L

Pressure in tank: pressure

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 3 Bar

Max. temperature (°C): 133 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 250 L

Max Overpressure: 3 Bar

Max. working temperature: 144 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: available

Agitator: yes

Number of revolutions: 80 - 400

Power: 1,10

Top: 5 mm

Cylinder: 5 mm

Bottom: 4 mm

Internal diameter tank: 990 mm

Outer diameter tank: 1.200 mm

Cylinder height: 1.430 mm

Total height of tank: 3.600 mm

SKU: 293596

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 133 °C

Mobil tank: Nej

Övrig information: Pharmacy; Tank was converted in 1987; manhole diameter 390 mm; further technical documents available; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees

Övrig information2: about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 3 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1200

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.430 mm

Invändig diameter: 990 mm

Total höjd: 3.600 mm

Ytterdiameter: 1.200 mm

Omrörare

Kraft (kW): 1,10

Varvtal: 80 - 400

Tjocklek på tank

Botten: 4 mm

Cylinder: 5 mm

Topp: 5 mm

Mer

Isolerad: Ja