

## 1200 liter tank i Syrafast 316



**95 000 SEK /st exkl moms**

**Article type:** second-hand mixing tank

**Additional information:** Previous product was various sauces; the tank was in use when purchased; the customer sold the tank because he needed a larger capacity; originally the agitator was equipped with scrapers but these are no longer included.; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

**Volumetric volume (L):** 1.200 L

**Pressure in tank:** ATM - atmosferic

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical



**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Top type:** half hinging lid

**Shape of tank:** cylindrical

**Bottom type:** conical

**Total discharge:** yes

**Fixation points:** 3 adjustable feet

**Type of HE on the cylinder:** dimple-jacket

**Water pressure HE:** 3 Bar

**Steam pressure HE:** 3 Bar

**Type of HE on the bottom:** dimple-jacket

**Water pressure HE:** 3 Bar

**Steam pressure HE:** 3 Bar

**Heat exchanger:** RVS 304

**Insulation material:** rockwool

**Outer jacket (ornamental wall):** RVS 304

**Fixation point(s):** RVS 304

**Wet parts agitator(s):** SS AISI 316 (V4A)

**Suitable for food industry:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**Outlet type:** DIN11851

**Agitator:** yes

**Agitator type:** gate

**Position engine:** at the top

**Number of revolutions:** ca 12

**Cylinder:** 3 mm

**Bottom:** 3 mm

**Cylinder:** 2

**Insulation body:** yes

**Bottom:** 2

**Insulation bottom/sides:** yes

**finish of the outer jacket:** welded

**Insulation thickness:** 50

**Internal diameter tank:** 1.200 mm

**Distance from outlet to ground:** 940 mm

**Outer diameter tank:** 1.300 mm

**Cylinder height:** 1.000 mm

**Height of top:** 2.150 mm

**Total height of tank:** 2.800 mm

**Empty weight tank:** 700

**SKU:** 484871

---

Mer information

## Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: Previous product was various sauces; the tank was in use when purchased; the customer sold the tank because he needed a larger capacity; originally the agitator was equipped with scrapers but these

Övrig information2: are no longer included.; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1200

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Livsmedelsklassad: Ja

Teknisk ritning finns: Nej

Utloppstyp: DIN11851

## Översikt material

Material: Syrafast 316

Fixeringspunkt(er): RVS 304

Isoleringsmaterial: Rockwool

Material vätskeberörd del på omrörare: SS AISI 316 (V4A)

Ytterbeklädnad: RVS 304

## **Dimensioner av tank**

Cylinderhöjd: 1.000 mm  
Invändig diameter: 1.200 mm  
Mått utlopp till marken: 940 mm  
Total höjd: 2.800 mm  
Ytterdiameter: 1.300 mm

## **Värmeväxlare**

Ångtryck värmeväxlare: 3 Bar  
Ångtryck värmeväxlare botten: 3 Bar  
Typ av värmeväxlare på cylinder: dimple-jacket  
Typ av värmeväxlare på botten: dimple-jacket  
Vattentryck värmeväxlare: 3 Bar  
Vattentryck värmeväxlare botten: 3 Bar

## **Omrörare**

Position motor: at the top  
Typ av omrörare: gate  
Varvtal: ca 12

## **Tjocklek på tank**

Botten: 3 mm  
Cylinder: 3 mm

## **Tjocklek på ytterbeklädnad och isolering**

Finish utvändig mantel: welded  
Isolering botten/gavlar: Ja  
Isolering mantel: Ja  
Isoleringsmaterial: Rockwool



## **Mer**

Värmeväxlare: RVS 304

Cylinder OW: 2

Botten OW: 2

Isoleringstjocklek OW: 50

Isolerad: Ja

Vikt: 700