12000 liter tank i Rostfritt 304



131 000 SEK /st exkl moms

Additional information: Sorbitol tank in the food industry; 1 partition wall (with openings) in the middle of the vessel divides the cylinder length of 5000 mm into 2 x 2,500 mm; lower area in the inner vessel straight instead of round due to the design; both vessel chambers with a 450 mm diameter manhole; 1 chamber with a DN 65 DIN 11851 outlet, the other with a DN 40 DIN 11851 outlet; product residue inside the vessel; 1 sheet metal cut-out at the top of the insulating jacket (see photos)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Volumetric volume (L): 12.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: horizontal

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Outlet of tank: available

Agitator: yes
Number of revolutions: 720
Power: 0,37
Internal diameter tank: 1.740 mm
Outer diameter tank: 1.850 mm

Total height of tank: 2.600 mm
Total outer length: 6.100 mm

SKU: 401849

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Horisontell
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated
Mobil tank: Nej
Övrig information: Sorbitol tank in the food industry; 1 partition (with openings) in the middle of the tank divides the cylinder length of 5000 mm into 2 x 2,500 mm; lower area in the inner tank straight instead of
Övrig information2:
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 12000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Invändig diameter: 1.740 mm
Total höjd: 2.600 mm
Ytterdiameter: 1.850 mm

Omrörare

Kraft (kW): 0,37
Varvtal: 720

Mer
Isolerad: Ja