

## 12000 liter tank i Rostfritt 304



**75 000 SEK /st exkl moms**

**Article type:** second-hand mixing tank

**Additional information:** dents in the top --> please look carefully at the pictures; we can't give any guarantees about the agitator

**Volumetric volume (L):** 12.000 L

**Pressure in tank:** ATM - atmosferic

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Top type:** conical

**Shape of tank:** cylindrical

**Bottom type:** conical

**Total discharge:** yes

**Fixation points:** 4 adjustable feet

**Insulation material:** Rockwool

**Outer jacket (ornamental wall):** RVS 304

**Manway(s):** RVS 304

**Gasket manway(s):** unknown

**Fixation point(s):** RVS 304

**Suitable for food industry:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**Number of manways:** 1

**Position of manway:** cylinder

**Height manhole 1 (mm):** 435 mm x H 315 mm

**Tank outlet:** inside Ø 40 mm

**Outlet type:** DIN11851 female

**Agitator:** yes

**Agitator type:** propeller agitator

**Position engine:** in the cylinder

**Number of revolutions:** 700

**Power:** 1,10

**Voltage:** three-phase

**finish of the outer jacket:** welded

**Insulation thickness:** 50

**Internal diameter tank:** 2.400 mm

**Distance from outlet to ground:** 400 mm

**Outer diameter tank:** 2.500 mm

**Cylinder height:** 2.700 mm  
**Total height of tank:** 4.100 mm  
**Empty weight tank:** 1.500

**SKU:** 92173

## Mer information

### Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: dents in the top -> please look carefully at the pictures; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 12000

## Utrustning

Dokument finns: Nej  
Fläns för omrörare: Nej  
Märkskylt: Nej  
Livsmedelsklassad: Ja  
Tankutlopp: inside Ø 40 mm  
Teknisk ritning finns: Nej  
Utloppstyp: DIN11851 female

## Översikt material

Material: Rostfritt 304  
Fixeringspunkt(er): RVS 304  
Isoleringsmaterial: Rockwool  
Ytterbeklädnad: RVS 304

## Dimensioner av tank

Cylinderhöjd: 2.700 mm  
Invändig diameter: 2.400 mm  
Mått utlopp till marken: 400 mm  
Total höjd: 4.100 mm  
Ytterdiameter: 2.500 mm

## Omrörare

Kraft (kW): 1,10  
Position motor: in the cylinder  
Typ av omrörare: propeller agitator  
Varvtal: 700  
Spänning (Volt): three-phase

## Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded  
Isoleringsmaterial: Rockwool

**Mer**

Isoleringstjocklek OW: 50

Isolerad: Ja

Vikt: 1.500