

12000 liter tank i Rostfritt 304



76,000,00 kr /st exkl moms

Article type: second-hand mixing tank

Additional information: dents in the top --> please look carefully at the pictures; we can't give any guarantees about the agitator

Volumetric volume (L): 12.000 L

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no



Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 4 adjustable feet

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: cylinder

Height manhole 1 (mm): 435 mm x H 315 mm

Tank outlet: inside Ø 40 mm

Outlet type: DIN11851 female

Agitator: yes

Agitator type: propeller agitator

Position engine: in the cylinder

Number of revolutions: 700

Power: 1,10

Voltage: three-phase

finish of the outer jacket: welded

Insulation thickness: 50

Internal diameter tank: 2.400 mm

Distance from outlet to ground: 400 mm

Outer diameter tank: 2.500 mm

Cylinder height: 2.700 mm

Total height of tank: 4.100 mm

Empty weight tank: 1.500

SKU: 92173

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: dents in the top -> please look carefully at the pictures; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 12000



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 40 mm
Teknisk ritning finns: Nej
Utloppstyp: DIN11851 female

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Isoleringsmaterial: Rockwool
Ytterbeklädnad: RVS 304

Dimensioner av tank

Cylinderhöjd: 2.700 mm
Invändig diameter: 2.400 mm
Mått utlopp till marken: 400 mm
Total höjd: 4.100 mm
Ytterdiameter: 2.500 mm

Omrörare

Kraft (kW): 1,10
Position motor: in the cylinder
Typ av omrörare: propeller agitator
Varvtal: 700
Spänning (Volt): three-phase

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded
Isoleringsmaterial: Rockwool



Mer

Isoleringstjocklek: 50

Isoleringstjocklek OW: 50

Isolerad: Ja

Vikt: 1.500