

12000 liter tank i Rostfritt 304



111,000,00 kr /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 12.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes



Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 4 adjustable feet

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: cylinder

Height manhole 1 (mm): 435 mm x H 315 mm

Tank outlet: inside Ø 40 mm

Outlet type: DIN11851 female

Agitator: yes

Agitator type: propeller agitator

Position engine: in the cylinder

Number of revolutions: 700

Power: 1,10

Voltage: three-phase

Insulation top: yes

Insulation body: yes

Insulation bottom/sides: yes

finish of the outer jacket: welded

Insulation thickness: 50

Internal diameter tank: 2.400 mm
Distance from outlet to ground: 400 mm
Outer diameter tank: 2.500 mm

Cylinder height: 2.700 mm
Total height of tank: 4.100 mm
Empty weight tank: 1.500

SKU: 92221

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nyttillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated
Mobil tank: Nej
Övrig information: we can't give any guarantees about the agitator
Omrörare: Ja
Tankens form: cylindrical
Total urtappning: Ja
Typ av botten: conical
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 12000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 40 mm
Teknisk ritning finns: Nej
Utloppstyp: DIN11851 female

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Isoleringsmaterial: Ja
Material vätskeberörd del på omrörare: SS AISI 304 (V2A)
Ytterbeklädnad: RVS 304

Dimensioner av tank

Cylinderhöjd: 2.700 mm
Invändig diameter: 2.400 mm
Mått utlopp till marken: 400 mm
Total höjd: 4.100 mm
Ytterdiameter: 2.500 mm

Omrörare

Kraft (kW): 1,10
Position motor: in the cylinder
Typ av omrörare: propeller agitator
Varvtal: 700
Spänning (Volt): three-phase

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded
Isolering botten/gavlar: Ja
Isolering mantel: Ja
Isoleringsmaterial: Ja



Mer

Isoleringsmaterial: Ja
Isoleringstjocklek: 50
Isoleringstjocklek OW: 50
Isolerad: Ja
Vikt: 1.500