

12000 liter tank i Rostfritt 304



142,000,00 kr /st exkl moms

Additional information: Sterile pressure tank in a dairy; Nameplate not available; 2 feet with load cells under the foot plates, 2 feet without height-adjustable screws, foot plate and load cells (see photos); pipe end cut flush

Volumetric volume (L): 12.000 L

Pressure in tank: pressure

Max. pressure (Bar): 3,50 Bar

Max. temperature (°C): 143 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Max Overpressure: 3,50 Bar

Type HE on the bottom: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 65

Cylinder: 4 mm

Bottom: 8 mm

Internal diameter tank: 2.500 mm

Cylinder height: 2.000 mm

Total height of tank: 3.750 mm

SKU: 286877

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 143 °C

Mobil tank: Nej

Övrig information: Sterile pressure tank in a dairy; Nameplate not available; 2 feet with load cells under the foot plates, 2 feet without height-adjustable screws, foot plate and load cells (see photos); pipe end

Övrig information2: cut flush

Omrörare: Nej

Övertryck: 3,50 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 12000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 2.000 mm

Invändig diameter: 2.500 mm

Total höjd: 3.750 mm

Tjocklek på tank

Botten: 8 mm

Cylinder: 4 mm

Mer

Värmeväxlare: RVS 304

Isolerad: Nej