120000 liter tank i Syrafast 316



474 000 SEK /st exkl moms

Additional information: Manhole diameter: 500 mm; some residues of previous content
Volumetric volume (L): 120.000 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 100 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: cylinder
Outlet of tank: available
Top: 4 mm
Cylinder: 4 mm
Bottom: 8 mm

Internal diameter tank: 3.500 mm
Cylinder height: 11.500 mm
Total height of tank: 13.600 mm
Empty weight tank: 5.500

SKU: 568823

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: single-skin
Max. arbetstemperatur: 100 °C
Mobil tank: Nej
Övrig information: Manhole diameter: 500 mm; some residues of previous content
Omrörare: Nej
Total urtappning: Yes
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 120000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 11.500 mm
Invändig diameter: 3.500 mm
Total höjd: 13.600 mm

Tjocklek på tank

Botten: 8 mm
Cylinder: 4 mm
Topp: 4 mm

Mer
Isolerad: Nej
Vikt: 5.500