

120000 liter tank i Syrafast 316



470,000,00 SEK /st exkl moms

Additional information: Manhole diameter: 500 mm; some residues of previous content

Volumetric volume (L): 120.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: available

Top: 4 mm

Cylinder: 4 mm

Bottom: 8 mm

Internal diameter tank: 3.500 mm

Cylinder height: 11.500 mm

Total height of tank: 13.600 mm

Empty weight tank: 5.500

SKU: 568823

Mer information



Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: Manhole diameter: 500 mm; some residues of previous content

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 120000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 11.500 mm

Invändig diameter: 3.500 mm

Total höjd: 13.600 mm

Tjocklek på tank

Botten: 8 mm

Cylinder: 4 mm

Topp: 4 mm

Mer

Isolerad: Nej

Vikt: 5.500
