

1212 liter tank i Rostfritt 304



99 000 SEK /st exkl moms

Additional information: solvent; the double jacket is used as a protective jacket with leak monitoring

Volumetric volume (L): 1.212 L

Pressure in tank: ATM - atmosferic

Max. pressure (Bar): 4 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 50 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: no

Max Overpressure: 4 Bar

Max onderdruk: 1 Bar

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

SKU: 313211

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 50 °C

Mobil tank: Nej

Övrig information: solvent; the double jacket is used as a protective jacket with leak monitoring

Omrörare: Nej

Övertryck: 4 Bar

Total urtappning: Nej

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 1212

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Mer

Isolerad: Nej