

## 1229 liter tank i Syrafast 316



**220,000,00 kr /st exkl moms**

**Additional information:** Pharmacy; Tank was rebuilt in 2011; further technical documents available

**Volumetric volume (L):** 1.229 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 150 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 88 L

**Max Overpressure:** 3 Bar

**Max. working temperature:** 150 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** 30

**Top:** 6,50 mm

**Cylinder:** 8 mm

**Bottom:** 5,70 mm

**Internal diameter tank:** 1.188 mm

**Outer diameter tank:** 1.347 mm

**Cylinder height:** 750 mm

**Total height of tank:** 2.350 mm

**SKU:** 294562

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Pharmacy; Tank was rebuilt in 2011; further technical documents available; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1229

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

## **Dimensioner av tank**

Cylinderhöjd: 750 mm  
Invändig diameter: 1.188 mm  
Total höjd: 2.350 mm  
Ytterdiameter: 1.347 mm

## **Tjocklek på tank**

Botten: 5,70 mm  
Cylinder: 8 mm  
Topp: 6,50 mm

## **Mer**

Isolerad: Ja