

124 liter tank i Syrafast 316



51 000 SEK /st exkl moms

Additional information: pharmacy; Filling pipe inside the tank (see pictures); GEMÜ bottom outlet diaphragm valve at the outlet. Technical documentation available from the manufacturer.

Volumetric volume (L): 124 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 14 L

Max Overpressure: 2 Bar

Max onderdruk: 1 Bar

Max. working temperature: 50 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: clamp

Internal diameter tank: 500 mm

Cylinder height: 680 mm

Total height of tank: 1.250 mm

SKU: 481714

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: pharmacy; Filling pipe inside the tank (see pictures); GEMÜ bottom outlet diaphragm valve at the outlet. Technical documentation available from the manufacturer.; we can't give any guarantees about

Övrig information2: the heating/cooling jacket

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 124

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 680 mm

Invändig diameter: 500 mm

Total höjd: 1.250 mm

Mer

Värmeväxlare: RVS 304

Isolerad: Ja