

1240 liter tank i Rostfritt 304



189 000 SEK /st exkl moms

Additional information: Make: Unimix; manhole DN 350; test papers in French; Outlet flange inner diameter 127 mm (reduced to outlet DN 40 DIN 11851 due to several fittings)

Volumetric volume (L): 1.240 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 143 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 82 L

Max Overpressure: 4 Bar

Max onderdruk: 1 Bar

Max. working temperature: 151 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: available

Agitator: yes

Number of revolutions: 17 / 34

Power: 13.5 / 21

Cylinder: 10 mm

Bottom: 8 mm

Internal diameter tank: 1.154 mm

Outer diameter tank: 1.380 mm

Cylinder height: 822 mm

Total height of tank: 3.650 mm

SKU: 277762

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 143 °C

Mobil tank: Nej

Övrig information: Make: Unimix; manhole DN 350; test papers in French; Outlet flange inner diameter 127 mm (reduced to outlet DN 40 DIN 11851 due to several fittings); we can't give any guarantees about the

Övrig information2: heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 1240

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 822 mm

Invändig diameter: 1.154 mm

Total höjd: 3.650 mm

Ytterdiameter: 1.380 mm

Omrörare

Kraft (kW): 13.5 / 21

Varvtal: 17 / 34

Tjocklek på tank

Botten: 8 mm

Cylinder: 10 mm

Mer

Isolerad: Ja