

12400 liter tank i Rostfritt 304



155,000,00 kr /st exkl moms

Additional information: Food industry; Half-coils around approx. 1.500 mm of the cylinder height; 1 strong dent in the insulating jacket; 1 railing around the upper bottom (slightly bent)

Volumetric volume (L): 12.400 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 95 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Max Overpressure: 3 Bar

Max. working temperature: 20 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 693

Power: 4

Internal diameter tank: 1.890 mm

Outer diameter tank: 2.050 mm

Cylinder height: 4.150 mm

Total height of tank: 6.450 mm

SKU: 287630

Mer information
