

1250 liter tank i Rostfritt 304



27,000,00 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: Extra outlet with butterfly valve is €425; we can't give any guarantees about the agitator

Volumetric volume (L): 1.250 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: flat

Shape of tank: rectangular

Bottom type: flat

Total discharge: no

Fixation points: 4 stackable frame

Manway(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)

Suitable for food industry: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top
Height manhole 1 (mm): 385 mm

Agitator: yes
Position engine: at the top
Number of revolutions: 250
Power: 1,10
Voltage: three-phase

Cylinder height: 1.160 mm
Total height of tank: 2.350 mm
Total outer width: 1.015 mm
Total outer length: 1.215 mm
Empty weight tank: 300

SKU: 572414

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: Extra outlet with butterfly valve is €425; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: rectangular

Total urtappning: Nej

Typ av botten: flat

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 1250

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Dimensioner av tank

Cylinderhöjd: 1.160 mm

Total höjd: 2.350 mm

Omrörare

Kraft (kW): 1,10

Position motor: at the top

Varvtal: 250

Spänning (Volt): three-phase

Mer

Isolerad: Nej

Vikt: 300