1250 liter tank i Rostfritt 304



28 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: Extra outlet with butterfly valve is €425; we can't give any guarantees about the agitator
Volumetric volume (L): 1.250 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no

Mobile tank: no

Top type: flat
Shape of tank: rectangular
Bottom type: flat
Total discharge: no
Fixation points: 4 stackable frame

Manway(s): RVS 304
Wet parts agitator(s): SS AISI 304 (V2A)
Suitable for food industry: no
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 385 mm

Agitator: yes
Position engine: at the top
Number of revolutions: 250
Power: 1,10
Voltage: three-phase

Cylinder height: 1.160 mm
Total height of tank: 2.350 mm
Total outer width: 1.015 mm
Total outer length: 1.215 mm
Empty weight tank: 300

SKU: 572414

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: Extra outlet with butterfly valve is €425; we can't give any guarantees about the agitator
Omrörare: Ja
Tankens form: rectangular
Total urtappning: Nej
Typ av botten: flat
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 1250

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304
Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Dimensioner av tank

Cylinderhöjd: 1.160 mm
Total höjd: 2.350 mm

Omrörare

Kraft (kW): 1,10
Position motor: at the top
Varvtal: 250
Spänning (Volt): three-phase

Mer

Isolerad: Nej
Vikt: 300