

1250 liter tank i Syrafast 316



25,000,00 SEK /st exkl moms

Additional information: Frame, Aisi 304 (1.4541); internal dimensions approx. 950 x 1,165 mm; wall height approx. 1,150 mm; manhole diameter approx. 440 mm; traces of usage

Volumetric volume (L): 1.250 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN65 DIN 11851

Total height of tank: 1.750 mm

Total outer width: 1.040 mm

Total outer length: 1.250 mm

SKU: 484286

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: Frame, Aisi 304 (1.4541); internal dimensions approx. 950 x 1,165 mm; wall height approx. 1,150 mm; manhole diameter approx. 440 mm; traces of usage

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1250

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Total höjd: 1.750 mm

Mer

Isolerad: Nej