1250 liter tank i Syrafast 316



187 000 SEK /st exkl moms

Additional information: Food industry; Agitators, Aisi 304 (1.4301); 1 rectangular opening approx. 410 x 540 mm in the upper bottom; some residues of previous content
Volumetric volume (L): 1.250 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no

Total discharge: yes
Volume: 8 L
Max Overpressure: 6 Bar
Max. working temperature: 260 °C
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: 70
Agitator: yes

Number of revolutions: 456
Power: 3
Internal diameter tank: 1.240 mm
Outer diameter tank: 1.400 mm
Cylinder height: 1.000 mm

Total height of tank: 3.100 mm
Empty weight tank: 750

SKU: 411194

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 80 °C
Mobil tank: Nej
Övrig information: Food industry; Agitators, Aisi 304 (1.4301); 1 rectangular opening approx. 410 x 540 mm in the upper bottom; some residues of previous content; we can't give any guarantees about the heating/cooling
Övrig information2: jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1250

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.000 mm
Invändig diameter: 1.240 mm
Total höjd: 3.100 mm
Ytterdiameter: 1.400 mm

Omrörare
Kraft (kW): 3
Varvtal: 456

Mer
Isolerad: Ja
Vikt: 750