

12500 liter tank i Syrafast 316



148 000 SEK /st exkl moms

Additional information: Chemistry; 4 support brackets, Fe (1 x 1 piece of the support plate cut off); 2 of the former 4 baffles inside the tank were cut off by the previous operator (see photos); some residues of previous content; manhole cover plated

Volumetric volume (L): 12.500 L

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)
Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom

Outlet of tank: 50
Agitator: yes
Number of revolutions: 58 - 200
Top: 4,80 mm
Cylinder: 4 mm

Bottom: 3,80 mm
Internal diameter tank: 2.200 mm
Cylinder height: 2.800 mm
Total height of tank: 5.500 mm

SKU: 275557

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: Chemistry; 4 support brackets, Fe (1 x 1 piece of the support plate cut off); 2 of the former 4 baffles inside the tank were cut off by the previous operator (see photos) ; some residues of previous

Övrig information2: content;manhole cover plated; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 12500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.800 mm

Invändig diameter: 2.200 mm

Total höjd: 5.500 mm

Omrörare

Varvtal: 58 – 200

Tjocklek på tank

Botten: 3,80 mm

Cylinder: 4 mm

Topp: 4,80 mm

Mer

Isolerad: Nej