12500 liter tank i Syrafast 316



100 000 SEK /st exkl moms

Additional information: textile industry; Flanges (not in contact with the product) partly made of mild steel; manhole diameter 600 mm; manhole cover plated
Volumetric volume (L): 12.500 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: no

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: cylinder

Outlet of tank: non-existent
Top: 5,70 mm
Cylinder: 5,20 mm
Bottom: 5,30 mm
Internal diameter tank: 2.500 mm

Cylinder height: 2.200 mm
Total height of tank: 3.300 mm
Empty weight tank: 1.500

SKU: 452846

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: textile industry; Flanges (not in contact with the product) partly made of mild steel; manhole diameter 600 mm; manhole cover plated
Omrörare: Nej
Total urtappning: Nej
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 12500

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.200 mm
Invändig diameter: 2.500 mm
Total höjd: 3.300 mm

Tjocklek på tank

Botten: 5,30 mm
Cylinder: 5,20 mm
Topp: 5,70 mm

Mer
Isolerad: Nej
Vikt: 1.500

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se