1260 liter tank i Rostfritt 304



45 000 SEK /st exkl moms

Additional information: Food utilization; 2 bearing shells, Fe; test pressure (water): 1 bar; 3 openings diameter tube inside approx. 315 mm in the bottoms (1x with plated cover); 1 baffle plate inside the tank (see photos); some residues of previous content
Volumetric volume (L): 1.260 L
Pressure in tank: vacuum

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar
Max. temperature (°C): 110 °C

Material wet parts: SS AISI 304 (V2A)
Model: horizontal
Configuration: single-skin
Heat exchanger: no
Insulation: no

Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Outlet of tank: available
Cylinder: 5,10 mm
Bottom: 5,40 mm
Internal diameter tank: 990 mm

Total height of tank: 1.350 mm
Total outer length: 2.150 mm

SKU: 420668

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Horisontell
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 110 °C
Mobil tank: Nej
Övrig information: Food utilization; 2 bearing shells, Fe; Test pressure (water): 1 bar; 3 openings diameter tube inside approx. 315 mm in the bottoms (1x with plated cover); 1 baffle plate inside the tank (see
Övrig information2: photos) ; some residues of previous content
Omrörare: Nej
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 1260

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Invändig diameter: 990 mm
Total höjd: 1.350 mm

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tjocklek på tank
Botten: 5,40 mm
Cylinder: 5,10 mm

Mer
Isolerad: Nej