1260 liter tank i Syrafast 316



70 000 SEK /st exkl moms

Additional information: chemistry; 1 strong dent in the insulation jacket; some residues of previous content
Volumetric volume (L): 1.260 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 4 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 106 L
Max Overpressure: 2,50 Bar

Max onderdruk: 1 Bar
Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: DN40 DIN 11851

Internal diameter tank: 1.080 mm
Outer diameter tank: 1.250 mm
Cylinder height: 1.100 mm
Total height of tank: 2.900 mm

SKU: 394946

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: isolert med varmeveksler
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: chemistry; 1 strong dent in the insulation jacket; some residues of previous content; we can’t give any guarantees about the heating/cooling jacket
Omrörare: Nej
Övertryck: 4 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1260

Utrustning

Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.100 mm
Invändig diameter: 1.080 mm
Total höjd: 2.900 mm
Ytterdiameter: 1.250 mm

Mer

Isolerad: Ja