

12600 liter tank i Syrafast 316



236 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type K3-H12W.L

Volumetric volume (L): 12.600 L

Max. density P (kg/m³): 1.200

Ra inner weld: 0,80

Finish stainless steel: 2b

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 100 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 316L (V4A)



Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Top type: conical 15 °

Shape of tank: cylindrical

Bottom type: conical 15 °

Total discharge: yes

Fixation points: 4 adjustable feet

Type of HE on the cylinder: dimple-jacket

Position HE: the complet cilinder

Height HE: 2.500 mm

Number of sections: 3

Height per section: 750 mm

Water pressure HE: 3 Bar

Steam pressure HE: 0,50 Bar

Contact surface cylinder: 16,50 m²

Connection HE: 1" BSP

Working temperature HE cylinder: 110 °C

Type of HE on the bottom: dimple-jacket

Water pressure HE: 3 Bar

Steam pressure HE: 0,50 Bar

Contact surface bottom: 1,50

Connection HE: 1" BSP

Working temperature HE bottom: 110 °C

Heat exchanger: RVS 304

Manway(s): RVS 316

Gasket manway(s): EPDM

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Inspection of: TUV

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

CIP spray ball: no, optional

Tank outlet: inside Ø 65 mm

Outlet type: DIN11851 male

Agitator: no, optional

Top: 2 mm

Cylinder: 2,50 mm

Bottom: 2,50 mm

Distance from outlet to ground: 356 mm

Outer diameter tank: 2.150 mm

Cylinder height: 3.250 mm

Feet height: 710 mm

Total height of tank: 4.320 mm

Empty weight tank: 750

SKU: 11892

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Syrafast 316
Modell: Vertikal
Nyttillverkad/Begagnad: Nyttillverkad
Arbetstryck i tank: ATM – atmosferic
Finish rostfritt stål: 2b
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 100 °C
Maximal densitet för produkten: 1200
Min. arbetstemperatur: -10 °C
Mobil tank: Nej
Omrörare: Nej
Ra innersvets: 0,80
Tankens form: cylindrical
Total urtappning: Ja
Typ av botten: conical 15 °
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316L (V4A)
Volym i liter: 12600

Utrustning

Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
med besiktning av: TUV
Tankutlopp: inside Ø 65 mm
Teknisk ritning finns: Ja
Utloppstyp: DIN11851 male

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 3.250 mm

Höjd på fötter: 710 mm

Mått utlopp till marken: 356 mm

Total höjd: 4.320 mm

Ytterdiameter: 2.150 mm

Värmeväxlare

Ångtryck värmeväxlare: 0,50 Bar

Ångtryck värmeväxlare botten: 0,50 Bar

Anslutning värmeväxlare: 1" BSP

Anslutning värmeväxlare botten: 1" BSP

Arbetstemperatur värmeväxlare cylinder: 110 °C

Arbetstemperatur värmeväxlare botten: 110 °C

Höjd värmeväxlare: 2.500 mm

Kontaktyta botten: 1,50

Kontaktyta cylinder: 16,50 m²

Position värmeväxlare: the complet cilinder

Typ av värmeväxlare på cylinder: dimple-jacket

Typ av värmeväxlare på botten: dimple-jacket

Vattentryck värmeväxlare: 3 Bar

Vattentryck värmeväxlare botten: 3 Bar

Tjocklek på tank

Botten: 2,50 mm

Cylinder: 2,50 mm

Topp: 2 mm

Mer

Värmeväxlare: RVS 304

Isolerad: Nej

Vikt: 750