

## 1270 liter tank i Rostfritt 304



**88 000 SEK /st exkl moms**

**Additional information:** Dairy; Possibly also double casing or former double casing around the lower base; lower base of the inner tank with smaller dents

**Volumetric volume (L):** 1.270 L

**Pressure in tank:** ATM - atmosferic



**Max. temperature (°C):** 95 °C

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 20 L

**Max Overpressure:** 3 Bar

**Max. working temperature:** 95 °C

**Type HE on the cylinder:** heating/cooling jacket

**Heat exchanger:** RVS 304

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** flange DN50

**Agitator:** yes

**Number of revolutions:** 25 / 49

**Power:** 0.3 / 0.6

**Internal diameter tank:** 1.180 mm

**Outer diameter tank:** 1.320 mm

**Cylinder height:** 970 mm

**Total height of tank:** 2.650 mm

**SKU:** 486326

## Mer information

### Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 95 °C

Mobil tank: Nej

Övrig information: Dairy; Possibly also double jacket or former double jacket around the lower bottom; lower bottom of the inner tank with smaller dents; we can't give any guarantees about the heating/cooling jacket;

Övrig information2: we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 1270

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Rostfritt 304

## Dimensioner av tank

Cylinderhöjd: 970 mm  
Invändig diameter: 1.180 mm  
Total höjd: 2.650 mm  
Ytterdiameter: 1.320 mm

## Omrörare

Kraft (kW): 0.3 / 0.6  
Varvtal: 25 / 49

## Mer

Värmeväxlare: RVS 304  
Isolerad: Ja