

12800 liter tank i Syrafast 316



58,000,00 kr /st exkl moms

Additional information: adhesive production; 4 support brackets Fe; diameter manhole 580 mm; slight metallic discolourations inside; total height tank 1: appr. 5450 mm (this tank with diverse internal installations, see pictures); total height tank 2: appr. 4650 mm (baffles inside); some residues of previous content; manhole cover plated

Volumetric volume (L): 12.800 L

Pressure in tank: pressure

Max. pressure (Bar): 0,90 Bar

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: yes

Position of manway: headside

Outlet of tank: 47

Top: 6,80 mm

Cylinder: 6,50 mm

Bottom: 6,30 mm

Internal diameter tank: 2.190 mm

Cylinder height: 2.800 mm

SKU: 269662

Mer information



Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure

Konfiguration: single-skin

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: adhesive production; 4 support brackets Fe; diameter manhole 580 mm; slight metallic discolourations inside; total height tank 1: appr. 5450 mm (this tank with diverse internal installations, see

Övrig information2: pictures); total height tank 2: appr. 4650 mm (baffles inside); some residues of previous content; manhole cover plated

Omrörare: Nej

Övertryck: 0,90 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 12800

Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.800 mm

Invändig diameter: 2.190 mm

Tjocklek på tank

Botten: 6,30 mm

Cylinder: 6,50 mm

Topp: 6,80 mm

Mer

Isolerad: Nej