130 liter tank i Syrafast 316



PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

29 000 SEK /st exkl moms

Additional information: Diameter of hand hole approx. 150 mm; dip tubes inside the tanks; some minor dents
Volumetric volume (L): 130 L
Pressure in tank: pressure
Max. pressure (Bar): 1,50 Bar
Min. pressure (Bar): 1,50 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: no
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: non-existent
Internal diameter tank: 490 mm
Total height of tank: 980 mm

SKU: 391973

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single-skin
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Diameter of hand hole approx. 150 mm; dip tubes inside the tanks; some minor dents
Omrörare: Nej
Övertryck: 1,50 Bar
Total urtappning: Nej
Undertryck (vakuum): 1,50 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 130

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 490 mm
Total höjd: 980 mm

Mer
Isolerad: Nej