

130 liter tank i Syrafast 316



28 000 SEK /st exkl moms

Additional information: Diameter of hand hole approx. 150 mm; dip tubes inside the tanks; some minor dents

Volumetric volume (L): 130 L

Pressure in tank: pressure

Max. pressure (Bar): 1,50 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: non-existent

Internal diameter tank: 490 mm

Total height of tank: 980 mm

SKU: 391973

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: single-skin

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Diameter of hand hole approx. 150 mm; dip tubes inside the tanks; some minor dents

Omrörare: Nej

Övertryck: 1,50 Bar

Total urtappning: Nej

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 130

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 490 mm

Total höjd: 980 mm

Mer

Isolerad: Nej
